

## Pyranometer Spectrally Flat Class B ISO9060



### Description

The pyranometers measure the global irradiance on a flat surface ( $W/m^2$ ); sum of direct solar irradiance and diffuse irradiance.

The PCTRA113 models falls within the Spectrally Flat Class B pyranometers according to the ISO 9060:2018 standard and meets the requirements of the WMO "Guide to Instruments and Methods of Observation".

The internal temperature, relative humidity and pressure diagnostic sensors integrated allow keeping the pyranometer operating conditions under control all the time and foresee any maintenance work in advance, thus ensuring always reliable measurements.

The integrated bubble level and the adjustable feet facilitate horizontal positioning during installation. As option, the pyranometers can be equipped with a tilt sensor which, in addition to facilitating the installation of the pyranometer, allows continuous monitoring of the correct installation. The various models are distinguished by the type of output available and by the presence or absence of the "tilt" sensor

The irradiance range for the analog output is user configurable.

The pyranometers are factory calibrated in accordance with the ISO 9847:2023 (Type A1) standard: "Calibration of pyranometers by comparison to a reference pyranometer". The calibration is performed by comparison with the reference sample calibrated annually at WRC (World Radiation Center).



Piranometro Spectrally Flat Class B



Piranometro - esempio applicativo

Technical specifications may be varied without prior notice

## Technical specifications

<b>Sensor</b>	Thermopile
<b>Measuring range</b>	-200...4000W/m <sup>2</sup> The irradiance range for the analog output is 0...2000 W/m <sup>2</sup> by default, and is configurable
<b>Resolution</b>	0,1 W/m <sup>2</sup>
<b>Viewing angle</b>	2π sr
<b>Spectral range (50%)</b>	283...2800 nm
<b>Output</b>	RS485 Modbus-RTU (isolata) Added optional configurable analog output 4...20 mA (default), 0...20 mA, 0...1 V, 0...5 V o 0...10 V
<b>Power supply</b>	7...30 Vdc for RS485 output 10...30 Vdc for analog output (except 0...10V) 15...30 Vdc for 0...10 V output
<b>Consumption</b>	15 mA @ 24 Vdc
<b>Connection</b>	M12 5 poles (version with only one RS485 Modbus —RTU output) M12 8 poles (version with an added analog output)
<b>Weight</b>	620 g ca.
<b>Operating conditions</b>	-40... +80°C/0...100% UR
<b>Bubble level accuracy</b>	< 0,2°
<b>Protection degree</b>	IP 67
<b>Materials</b>	Housing: anodized aluminium - Screen: ASA - Dome: optical glass
<b>MTBF</b>	> 10 years

### Technical Specifications according to ISO 9060:2018

<b>Classification</b>	Spectrally Flat Class B
<b>Response time (95%)</b>	< 2 s
<b>Zero off-set</b>	- response to a 200 W/m <sup>2</sup> thermal radiation: < ±7 W/m <sup>2</sup> - response to a 5 K/h change in ambient temperature: < ±2 W/m <sup>2</sup> - total zero offset including the effects a), b) and other sources: < ±10 W/m <sup>2</sup>
<b>Long-term instability (1 year)</b>	<  ±0,5  %
<b>Non-linearity</b>	<  ± 0,2  %
<b>Directional response (up to 80° with 1000 W/m<sup>2</sup> beam)</b>	<  ±10  W/m <sup>2</sup>
<b>Spectral error</b>	<  ±0,2  %
<b>Temperature response</b>	<  ±0,5  %
<b>Tilt response</b>	<  ±0,2  %
<b>Diagnostic sensors</b>	
<b>Internal Temperature</b>	Measuring range: -40...+80°C; Resolution: 0,1°C; Accuracy: ± 0,5°C (0...60°C)
<b>Internal Relative Humidity</b>	Measuring range: 0...100 %UR; Resolution: 0,1 %UR; Accuracy: ± 3 %UR @25°C (20...80 %UR)
<b>Internal pressure</b>	Measuring range: 300... 1100 hPa; Resolution: 0,1 hPa; Accuracy: ±1 hPa (0...60%)
<b>Tilt sensor</b>	Measuring range: 0°...+180°; Resolution: 0,1°; Accuracy: < 0,5°

## Ordering codes

Global radiation sensor Class B with mV output	<b>PCTRA113</b>
Global radiation sensor Class B with 4...20mA output	<b>PCTRA114</b>
Global radiation sensor Class B with modbus output	<b>PCTRA115</b>
Global radiation sensor Class B with modbus output with tilt option	<b>PCTRA116</b>
Global radiation sensor Class B with modbus and analog outputs	<b>PCTRA117</b>
Global radiation sensor Class B with modbus and analog outputs with tilt option	<b>PCTRA118</b>

Technical specifications may be varied without prior notice